



VIVAfloors

Eiken - Oak - Eiche **7000**

Eiken - Oak - Eiche

Specificaties - Specifications - Technische Daten

NL	EN	DU		Lijmversie Glue down Kleber	Clickversie Click Klick
Specificaties	Specifications	Technische Daten			
Totale dikte	Total Thickness	Gesamtstärke	EN 428	2,5 mm	6,5 mm <i>Inclusief ondervloer Subfloor included Inklusive Uterlage</i>
Dikte van de slijtlaag	Wear layer	Nutzschicht	EN 429	0,55 mm	0,55 mm
Dikte geluiddempende IXPE ondervloer	Thickness soundinsulating IXPE underlay	Stärke trittschall IXPE untergrund	-	-	1 mm
Totaal gewicht	Total Weight	Total Gewicht	EN 430	4,53 kg/m ²	8,69 kg/m ²
Toplaag	Surface treatment	Oberflächenvergütung	Embossed	PUR	PUR
Afmeting	Dimension	Abmessung	EN 24342	152,4 x 22,9 cm	152,4 x 22,6 cm
Gebruikscategorie	Usage classification	Klassifizierung	EN 685	23, 33, 42	23, 33, 42
Clickverbinding	Locking System	Klickverbindung			2G-2G Vålinge
Testresultaten	Test Results	Testergebnisse			
Vloerverwarming	Underfloor heating	Fussbodenheizung	EN 12524	Suitable Max. 27 °C	Suitable Max. 27 °C
Warmte doorlaat weerstand	Thermal resistance	Wärmedurchlasswiderstand	EN 12667	0,015 m ² K/W	0,052 m ² K/W
Rolstoeltest	Castor Chair	Rollstuhl	EN 425	Pass	Pass
Brandklasse	Fire resistance	Brandverhalten	EN 13501-1	Bfl-s1	Bfl-s1
Weerstand chemische stoffen	Chemical resistance	Chemikalienbeständigkeit	EN 423	Good	Good
Restindruk	Residual indentation	Eindruckverhalten	EN ISO 24343-1	≤ 0,10 mm	≤ 0,15 mm
Slijptest	Slip resistance	Rutschhemmung	EN 13893	R10	R10
Krasvastheid	Abrasion class	Verschleißgruppe	EN 660-2	T	T
Geluidsabsorptie	Sound reduction	Reduzierung des Trittschalls	EN 717-2 ISO 10140	4 dB	19 dB EU-norm 5 dB NL-norm <i>(incl Secura LVT Click Smart ISO 10140 Delta Lin 10 dB.)</i>
Lichtechtheid	Lightfastness	Lichtechtheit	ISO 105-B02	Pass ≥ 6	Pass ≥ 6
Dimensionale stabiliteit	Dimensional stability	Massänderung	EN 23999	< 0,25%	< 0,25%
Afmeting	Dimension	Verlegemass	EN427	Pass	Pass
Toxiciteit	Toxic elements test	Toxicität	EN 71	Not toxic	Not toxic
Garantie	Warranty	Garantie		Residential 25 years Commercial 10 years	Residential 25 years Commercial 10 years

First edition 2023 - Specifications are subject to change



IAC Gold gecertificeerd
IAC Gold certified
IAC Gold zertifiziert