



tesa® Powerstrips Deco Self-Adhesive Strip Transparent

Product Information

BNR 58800, 58802, 58803

Product Description

Use transparent tesa Powerstrips Deco for residue-free window decoration and light decorative objects with the advantage of easy removal without leaving traces.

Product Features

- Transparent for unobtrusive fixation
- Maximum hold of up to 200g on smooth surfaces*
- Removable without trace thanks to the Powerstrips technology
- Limited UV-resistance (e.g. seasonal decoration)

*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous materials.

Application Fields

- How to apply - step by step:
1. Clean the surface with alcohol or silicone-free glass cleaner
 2. Apply tesa Powerstrips® Transparent DECO strip on the surface - press for 5 seconds minimum
 3. Fix object onto surface - press for 5 seconds minimum
 4. Make sure the tab can be accessed for removal

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|--------------------------------|--------|
| • Type of adhesive | synthetic rubber | • Holding power of strip up to | 0.2 Kg |
| • Total thickness | 650 µm | | |

Properties/Performance Values

- | | | | |
|-----------------------------|-----|------------------------|-----|
| • Ageing resistance (UV) | yes | • Residue free removal | yes |
| • Chemical resistance | no | • Solvent free | yes |
| • Hazard material | no | • UV resistant | yes |
| • Humidity resistance | no | • Water resistance | no |
| • Oil and grease resistance | no | • Waterproof | no |
| • Ozone resistance | yes | | |



tesa[®] Powerstrips Deco Self-Adhesive Strip Transparent

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=58800>